

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
9 October 2003 (09.10.2003)

PCT

(10) International Publication Number  
**WO 03/082512 A1**

- (51) International Patent Classification<sup>7</sup>: **B23K 31/02**, **B24B 39/00**
- (21) International Application Number: PCT/US03/08747
- (22) International Filing Date: 25 March 2003 (25.03.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/367,623 26 March 2002 (26.03.2002) US  
PCT/US02/35214 1 November 2002 (01.11.2002) US
- (71) Applicant (for all designated States except US): **SURFACE TECHNOLOGY HOLDINGS, LTD.** [US/US]; 6325 Hunters Trail, Cincinnati, OH 45246 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **PREVEY, Paul, S., III** [US/US]; 6325 Hunters Trail, Cincinnati, OH 45246 (US).
- (74) Agent: **SMITH, Mark F.**; 7577 Central Park Boulevard, Suite 102, Mason, OH 45040 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS AND METHOD FOR FORMING A WELD JOINT HAVING IMPROVED PHYSICAL PROPERTIES



(57) Abstract: The method and apparatus for performing the method of forming a weld joint of the present invention utilizes welding apparatus (100) having welded tool (102) and a compression tool (106) for inducing a layer of residual compressive stress along the surface of the weld line (18) and any heat affected regions with a controlled amount of cold working and surface hardening. In a preferred embodiment of the invention the compression tool (106) utilizes a single-point burnishing process to provide deep compression within the weld joint (20) with a minimal amount of cold working and surface hardening.



WO 03/082512 A1